

Filtrasan Pocket 15

FiltraSan™

Soft synthetic pocket filter with U-section galvanised steel frame and FiltraSan $^{\text{TM}}$ sanitizing filter bags in 200 g/m2 polyester fibre with progressive density on the air outlet side.

 $Filtra \textbf{San}^{^{\intercal M}} \text{ in collaboration with:}$








TECHNICAL SPECIFICATIONS AND USAGE LIMIT						
EFFICIENCY class (EN ISO 16890)	Group ISO ePM10 60%					
EFFICIENCY class (CEN EN779-2012)	M5					
AVERAGE gravimetric efficiency:	96%					
FILTER FABRIC basic weight:	200gr/mq					
THICKNESS	10-12 mm					
MAXIMUM WORKING temperature	100°C					
RELATIVE humidity	100%					
INITIAL pressure drop	58 Pa					
RECOMMENDED final pressure drop	250 Pa					
MAXIMUM pressure drop	400 Pa					
DUST collection capacity	730 gr/mq					
RECOMMENDED frontal air speed	1,5 m/s					
	class F1 - (DIN53438/3)					
FIRE reaction	class B2 - (DIN4102/1)					
	class M1 - NF-F-16-101					

Pressure Drops



SELECTION CHART							
Model [code]	Dimensions W x Dx H [mm]	Pocket [n]	Nominal flow rate [m²]	Filtering surface [m³/h]			
15TF/3.290.3	290 X 595 X 360	3	1.650	1,3			
15TF/5.490.3	490 X 595 X 360	5	2.750	2,1			
15TF/6.595.3	595 X 595 X 360	6	3.300	2,6			
15TF/3.290.5	290 X 595 X 500	3	2.300	1,8			
15TF/5.490.5	490 X 595 X 500	5	3.800	3,0			
15TF/6.595.5	595 X 595 X 500	6	4.500	3,6			

PRESSURE DROP DIAGRAM (Air Temperature 20°C)

Diagram

Pressure drop determining curve with a clean filter (Dp) based on percentage change in the flow rate or nominal speed.



∆p (Pa)

CERTIFICATIONS



FILTERING MEDIA

FiltraSan™ sanitizing antibacterial and anti-mould filtering media, Sanitized® tested and certified







APPLICATIONS

Fan coils, air treatment units.

PRODUCT DISPOSAL

Dispose of the product by separating the metal part from the filtering part. The CER code for disposal of the metal part is 120101. The CER code for disposal of the filtering part is 150202.

GREEN BUILDING

Thanks also to the support of GreenMap, products manufactured by Tecnica contribute to obtain the credits of the major international rating systems for sustainable buildings:



LEED

Contributes to credits: IP, EA, MR



WFI

Contributes to credits:
AIR, MATERIALS, COMMUNITY, INNOVATION



BREEAM

Contributes to credits: MAN, WST

For further details regarding the specific contributions to the credits indicated, contact Tecnica SrI

APPLICATIONS								
	118			®	REACH	RoHS	ſ'n	
OEM	Residential	Easy Pack	Mold resistant	Microorganism Resistance	REACH Certificate	RoHS Certificate	Industrial	Building
*	*							
Air conditioning	CMV							*On request

