



TERMOCLIP PTFE

Extremely lightweight flexible hose made of PTFE-coated fibreglass fabric and external galvanized steel wire helix. Resistant to both high and low temperatures, meteorological conditions and aggressive chemicals. The hose is highly flexible and compressible with high tensile strength. PTFE is very safe for users' health and has a non-stick surface.

TECHNICAL SPECIFICATIONS AND USAGE LIMIT

COLOR	LENGTH	WORKING TEMPERATURE	AXIAL COMPRESSIBILITY
Brown	3 or 6 m.	-150°C up to +250°C	6:1

PRODUCTION DIAMETERS

50	55	60	65	70	75	80	90	100	110	120	125	130	140	150	160	170	175	180	
200	215	225	250	275	300	315	325	350	375	400	450	500	550	600	700	800	900		

Diameters other than those indicated are available by prior feasibility check.

MAIN APPLICATIONS

Extraction of corrosive agents, solvents and paints. Paper and paint industry, chemical and pharmaceutical industries.

MAINTENANCE

Periodically check the state of wear of the hose and immediately replace it if damaged or broken. Pay maximum attention to the duct operating temperatures.

TECHNICAL DATA

DIAMETERS	OPERATING PRESSURE	OPERATING VACUUM	INSIDE CURVATURE RADIUS	WEIGHT
[mm]	[bar]	[bar]	[mm]	[gr/m]
50	0,85	0,32	30	400
60	0,68	0,222	36	500
75	0,47	0,14	45	600
80	0,43	0,125	48	600
100	0,3	0,08	60	600
110	0,258	0,066	66	700

DIAMETERS	OPERATING PRESSURE	OPERATING VACUUM	INSIDE CURVATURE RADIUS	WEIGHT
[mm]	[bar]	[bar]	[mm]	[gr/m]
120	0,224	0,056	72	700
125	0,21	0,05	75	800
150	0,157	0,036	90	900
160	0,14	0,031	96	900
180	0,117	0,025	108	1000
200	0,1	0,02	120	1200
250	0,07	0,013	175	1600
300	0,05	0,009	210	2100
350	0,04	0,007	245	2500
400	0,03	0,005	280	3100
500	0,02	0,003	400	4100

Data given in this table are approximate.

* Pressure and vacuum data based on +20°C room temperature.

GREEN BUILDING

Thanks also to the support of GreenMap, products manufactured by Tecnica srl contribute to obtain the credits of the major international rating systems for sustainable buildings:



LEED

Contributes to credits:

MR



WELL

Contributes to credits:

MATERIALS

For further details regarding the specific contributions to the credits indicated, contact Tecnica Srl.

APPLICATIONS

OEM	Smooth Surface	Flexibility	Working Temperature	Chemical Resistance	Warning	Tear Resistance	Calibrated diameters*	Compact version*
Industry	Non-magnetic*	Extractor Hoods						

*on request